EE 350 Engineering E & M

Handout 1 – Vector calculus review 1

Dr. Zhang @ ECE, MSU Mankato

Outline:

1. Maxwell's equations (recall)
   a. Electrostatics & Magnetostatics

$$\begin{cases} \left.\begin{matrix} \nabla \cdot \vec{D} = \rho_v \\ \nabla \times \vec{E} = 0 \end{matrix}\right\} & \text{Electrostatics (chapter 4)} \\ \left.\begin{matrix} \nabla \cdot \vec{B} = 0 \\ \nabla \times \vec{H} = \vec{J} \end{matrix}\right\} & \text{Magnetostatics (chapter 5)} \end{cases}$$

   b. Maxwell's equations (governing all EM phenomena)

$$\begin{cases} \nabla \cdot \vec{D} = \rho_v \\ \nabla \times \vec{E} = -\dfrac{\partial \vec{B}}{\partial t} \\ \nabla \cdot \vec{B} = 0 \\ \nabla \times \vec{H} = \vec{J} + \dfrac{\partial \vec{D}}{\partial t} \end{cases}$$

2. Abstractions of models in ECET
   Nature; physical laws; amp; digital; combinational circuits; clocked; ISA; languages; software systems; Amp: op amp; analog systems; toasters etc.

3. Engineering/modeling/simulation/design vs. Computer science/programming

4. Review of the basics of vectors
   In the framework w/o general relativity and special relativit → Newton's university/Euclidean space

5. Orthogonal coordinate systems
   1). Cartesian coordinates (review by yourself after class); 2). Cylindrical coordinates



$r_1 \sim$ radial distance
$\phi_1 \sim$ azimuth angle
$z_1 \sim$ same as in Cartesian



$$\Rightarrow \begin{cases} d\vec{S}_z = \hat{z}\, r\,dr\,d\phi \\ d\vec{S}_r = \hat{r}\, r\,d\phi\,dz \\ d\vec{S}_\phi = \hat{\phi}\, dr\,dz \\ dv = r\,dr\,d\phi\,dz \end{cases}$$

3). Spherical coordinates





$\Rightarrow \begin{cases} R_1 \sim \text{range coordinate} \\ \theta \sim \text{zenith angle} \\ \phi \sim \text{azimuth angle (same as in cylindrical)} \end{cases}$

$$\Rightarrow \begin{cases} d\vec{S}_R = \hat{r}\, dl_\theta dl_\phi = \hat{r} R^2 \sin\theta d\theta d\phi \\ d\vec{S}_\theta = \hat{\theta}\, dl_R dl_\phi = \hat{\theta} R \sin\theta\, dR d\phi \\ d\vec{S}_\phi = \hat{\phi}\, dl_R dl_\theta = \hat{\phi} R\, dR d\theta \\ dv = dl_R dl_\theta dl_\phi = R^2 \sin\theta dR d\theta \end{cases}$$

4). Summary of vector relations

	Cartesian Coordinates	Cylindrical Coordinates	Spherical Coordinates
Coordinate variables	x, y, z	r, ϕ, z	R, θ, ϕ
Vector representation, A =	$\hat{\mathbf{x}}A_x + \hat{\mathbf{y}}A_y + \hat{\mathbf{z}}A_z$	$\hat{\mathbf{r}}A_r + \hat{\boldsymbol{\phi}}A_\phi + \hat{\mathbf{z}}A_z$	$\hat{\mathbf{R}}A_R + \hat{\boldsymbol{\theta}}A_\theta + \hat{\boldsymbol{\phi}}A_\phi$
Magnitude of A, $\lvert A\rvert$ =	$\sqrt[+]{A_x^2 + A_y^2 + A_z^2}$	$\sqrt[+]{A_r^2 + A_\phi^2 + A_z^2}$	$\sqrt[+]{A_R^2 + A_\theta^2 + A_\phi^2}$
Position vector $\overrightarrow{OP_1}$ =	$\hat{\mathbf{x}}x_1 + \hat{\mathbf{y}}y_1 + \hat{\mathbf{z}}z_1$, for $P(x_1, y_1, z_1)$	$\hat{\mathbf{r}}r_1 + \hat{\mathbf{z}}z_1$, for $P(r_1, \phi_1, z_1)$	$\hat{\mathbf{R}}R_1$, for $P(R_1, \theta_1, \phi_1)$
Base vectors properties	$\hat{\mathbf{x}}\cdot\hat{\mathbf{x}} = \hat{\mathbf{y}}\cdot\hat{\mathbf{y}} = \hat{\mathbf{z}}\cdot\hat{\mathbf{z}} = 1$ $\hat{\mathbf{x}}\cdot\hat{\mathbf{y}} = \hat{\mathbf{y}}\cdot\hat{\mathbf{z}} = \hat{\mathbf{z}}\cdot\hat{\mathbf{x}} = 0$ $\hat{\mathbf{x}}\times\hat{\mathbf{y}} = \hat{\mathbf{z}}$ $\hat{\mathbf{y}}\times\hat{\mathbf{z}} = \hat{\mathbf{x}}$ $\hat{\mathbf{z}}\times\hat{\mathbf{x}} = \hat{\mathbf{y}}$	$\hat{\mathbf{r}}\cdot\hat{\mathbf{r}} = \hat{\boldsymbol{\phi}}\cdot\hat{\boldsymbol{\phi}} = \hat{\mathbf{z}}\cdot\hat{\mathbf{z}} = 1$ $\hat{\mathbf{r}}\cdot\hat{\boldsymbol{\phi}} = \hat{\boldsymbol{\phi}}\cdot\hat{\mathbf{z}} = \hat{\mathbf{z}}\cdot\hat{\mathbf{r}} = 0$ $\hat{\mathbf{r}}\times\hat{\boldsymbol{\phi}} = \hat{\mathbf{z}}$ $\hat{\boldsymbol{\phi}}\times\hat{\mathbf{z}} = \hat{\mathbf{r}}$ $\hat{\mathbf{z}}\times\hat{\mathbf{r}} = \hat{\boldsymbol{\phi}}$	$\hat{\mathbf{R}}\cdot\hat{\mathbf{R}} = \hat{\boldsymbol{\theta}}\cdot\hat{\boldsymbol{\theta}} = \hat{\boldsymbol{\phi}}\cdot\hat{\boldsymbol{\phi}} = 1$ $\hat{\mathbf{R}}\cdot\hat{\boldsymbol{\theta}} = \hat{\boldsymbol{\theta}}\cdot\hat{\boldsymbol{\phi}} = \hat{\boldsymbol{\phi}}\cdot\hat{\mathbf{R}} = 0$ $\hat{\mathbf{R}}\times\hat{\boldsymbol{\theta}} = \hat{\boldsymbol{\phi}}$ $\hat{\boldsymbol{\theta}}\times\hat{\boldsymbol{\phi}} = \hat{\mathbf{R}}$ $\hat{\boldsymbol{\phi}}\times\hat{\mathbf{R}} = \hat{\boldsymbol{\theta}}$
Dot product, A · B =	$A_xB_x + A_yB_y + A_zB_z$	$A_rB_r + A_\phi B_\phi + A_zB_z$	$A_RB_R + A_\theta B_\theta + A_\phi B_\phi$
Cross product, A × B =	$\begin{vmatrix} \hat{\mathbf{x}} & \hat{\mathbf{y}} & \hat{\mathbf{z}} \\ A_x & A_y & A_z \\ B_x & B_y & B_z \end{vmatrix}$	$\begin{vmatrix} \hat{\mathbf{r}} & \hat{\boldsymbol{\phi}} & \hat{\mathbf{z}} \\ A_r & A_\phi & A_z \\ B_r & B_\phi & B_z \end{vmatrix}$	$\begin{vmatrix} \hat{\mathbf{R}} & \hat{\boldsymbol{\theta}} & \hat{\boldsymbol{\phi}} \\ A_R & A_\theta & A_\phi \\ B_R & B_\theta & B_\phi \end{vmatrix}$
Differential length, $d\mathbf{l}$ =	$\hat{\mathbf{x}}\,dx + \hat{\mathbf{y}}\,dy + \hat{\mathbf{z}}\,dz$	$\hat{\mathbf{r}}\,dr + \hat{\boldsymbol{\phi}}r\,d\phi + \hat{\mathbf{z}}\,dz$	$\hat{\mathbf{R}}\,dR + \hat{\boldsymbol{\theta}}R\,d\theta + \hat{\boldsymbol{\phi}}R\sin\theta\,d\phi$
Differential surface areas	$d\mathbf{s}_x = \hat{\mathbf{x}}\,dy\,dz$ $d\mathbf{s}_y = \hat{\mathbf{y}}\,dx\,dz$ $d\mathbf{s}_z = \hat{\mathbf{z}}\,dx\,dy$	$d\mathbf{s}_r = \hat{\mathbf{r}}r\,d\phi\,dz$ $d\mathbf{s}_\phi = \hat{\boldsymbol{\phi}}\,dr\,dz$ $d\mathbf{s}_z = \hat{\mathbf{z}}r\,dr\,d\phi$	$d\mathbf{s}_R = \hat{\mathbf{R}}R^2\sin\theta\,d\theta\,d\phi$ $d\mathbf{s}_\theta = \hat{\boldsymbol{\theta}}R\sin\theta\,dR\,d\phi$ $d\mathbf{s}_\phi = \hat{\boldsymbol{\phi}}R\,dR\,d\theta$
Differential volume, $d\mathcal{V}$ =	$dx\,dy\,dz$	$r\,dr\,d\phi\,dz$	$R^2\sin\theta\,dR\,d\theta\,d\phi$

6. Transforms between coordinate systems

Table 2-2: Coordinate transformation relations.

Transformation	Coordinate Variables	Unit Vectors	Vector Components
Cartesian to cylindrical	$r = \sqrt[+]{x^2 + y^2}$ $\phi = \tan^{-1}(y/x)$ $z = z$	$\hat{\mathbf{r}} = \hat{\mathbf{x}}\cos\phi + \hat{\mathbf{y}}\sin\phi$ $\hat{\boldsymbol{\phi}} = -\hat{\mathbf{x}}\sin\phi + \hat{\mathbf{y}}\cos\phi$ $\hat{\mathbf{z}} = \hat{\mathbf{z}}$	$A_r = A_x\cos\phi + A_y\sin\phi$ $A_\phi = -A_x\sin\phi + A_y\cos\phi$ $A_z = A_z$
Cylindrical to Cartesian	$x = r\cos\phi$ $y = r\sin\phi$ $z = z$	$\hat{\mathbf{x}} = \hat{\mathbf{r}}\cos\phi - \hat{\boldsymbol{\phi}}\sin\phi$ $\hat{\mathbf{y}} = \hat{\mathbf{r}}\sin\phi + \hat{\boldsymbol{\phi}}\cos\phi$ $\hat{\mathbf{z}} = \hat{\mathbf{z}}$	$A_x = A_r\cos\phi - A_\phi\sin\phi$ $A_y = A_r\sin\phi + A_\phi\cos\phi$ $A_z = A_z$
Cartesian to spherical	$R = \sqrt[+]{x^2 + y^2 + z^2}$ $\theta = \tan^{-1}[\sqrt[+]{x^2 + y^2}/z]$ $\phi = \tan^{-1}(y/x)$	$\hat{\mathbf{R}} = \hat{\mathbf{x}}\sin\theta\cos\phi + \hat{\mathbf{y}}\sin\theta\sin\phi + \hat{\mathbf{z}}\cos\theta$ $\hat{\boldsymbol{\theta}} = \hat{\mathbf{x}}\cos\theta\cos\phi + \hat{\mathbf{y}}\cos\theta\sin\phi - \hat{\mathbf{z}}\sin\theta$ $\hat{\boldsymbol{\phi}} = -\hat{\mathbf{x}}\sin\phi + \hat{\mathbf{y}}\cos\phi$	$A_R = A_x\sin\theta\cos\phi + A_y\sin\theta\sin\phi + A_z\cos\theta$ $A_\theta = A_x\cos\theta\cos\phi + A_y\cos\theta\sin\phi - A_z\sin\theta$ $A_\phi = -A_x\sin\phi + A_y\cos\phi$
Spherical to Cartesian	$x = R\sin\theta\cos\phi$ $y = R\sin\theta\sin\phi$ $z = R\cos\theta$	$\hat{\mathbf{x}} = \hat{\mathbf{R}}\sin\theta\cos\phi + \hat{\boldsymbol{\theta}}\cos\theta\cos\phi - \hat{\boldsymbol{\phi}}\sin\phi$ $\hat{\mathbf{y}} = \hat{\mathbf{R}}\sin\theta\sin\phi + \hat{\boldsymbol{\theta}}\cos\theta\sin\phi + \hat{\boldsymbol{\phi}}\cos\phi$ $\hat{\mathbf{z}} = \hat{\mathbf{R}}\cos\theta - \hat{\boldsymbol{\theta}}\sin\theta$	$A_x = A_R\sin\theta\cos\phi + A_\theta\cos\theta\cos\phi - A_\phi\sin\phi$ $A_y = A_R\sin\theta\sin\phi + A_\theta\cos\theta\sin\phi + A_\phi\cos\phi$ $A_z = A_R\cos\theta - A_\theta\sin\theta$
Cylindrical to spherical	$R = \sqrt[+]{r^2 + z^2}$ $\theta = \tan^{-1}(r/z)$ $\phi = \phi$	$\hat{\mathbf{R}} = \hat{\mathbf{r}}\sin\theta + \hat{\mathbf{z}}\cos\theta$ $\hat{\boldsymbol{\theta}} = \hat{\mathbf{r}}\cos\theta - \hat{\mathbf{z}}\sin\theta$ $\hat{\boldsymbol{\phi}} = \hat{\boldsymbol{\phi}}$	$A_R = A_r\sin\theta + A_z\cos\theta$ $A_\theta = A_r\cos\theta - A_z\sin\theta$ $A_\phi = A_\phi$
Spherical to cylindrical	$r = R\sin\theta$ $\phi = \phi$ $z = R\cos\theta$	$\hat{\mathbf{r}} = \hat{\mathbf{R}}\sin\theta + \hat{\boldsymbol{\theta}}\cos\theta$ $\hat{\boldsymbol{\phi}} = \hat{\boldsymbol{\phi}}$ $\hat{\mathbf{z}} = \hat{\mathbf{R}}\cos\theta - \hat{\boldsymbol{\theta}}\sin\theta$	$A_r = A_R\sin\theta + A_\theta\cos\theta$ $A_\phi = A_\phi$ $A_z = A_R\cos\theta - A_\theta\sin\theta$